



Helmet Lock Installation Instructions

**Read ALL instructions BEFORE attempting to install this product. *Failing to follow these instructions could result in serious injury or damage to motorcycle*

**Advanced Sport Touring is not responsible for any injury or damage to property resulting from the use of this product*

Included with Luggage Rack: (2) Helmet Locks with attached brackets, (2) 30mm bolts, (2) M6 Locks Nuts

Tools you will need: 4mm & 5mm Hex Keys, 10mm open-ended wrench

1. Remove your saddlebags for easier installation.
2. Remove luggage rack by removing the four bolts and alignment sleeves holding it into position using a 5mm Hex Key. **(Fig. 1)**
3. Hold the Reflector so it doesn't fall to the ground. Remove the bolt holding one of the reflector brackets using a 4mm Hex key. **(Fig. 3)** Replace the bolt you just removed with the 30mm bolt included in the kit.
4. Put either Helmet Lock Bracket into position with the bolt through the top of the bracket. Either bracket will work on either side. Position the bracket as low on the bolt as possible on the bolt and start threading the nut onto the bolt. **(Fig 5.1)** This is an extremely tight placement and it may not be possible to thread the nut on the bolt by hand. Using a 10mm open-ended wrench will make this process easier. Tighten lock nut. **(Fig. 5.2)**
5. Repeat process on other side of the bike.
6. Double check that brake light bracket is secure. Re-install luggage rack. Torque luggage rack bolts to 18 ft-lbs.

