



Luggage Rack/Backrest Combo Installation Instructions

**Read ALL instructions BEFORE attempting to install Luggage Rack*

**Failing to follow these instructions could result in serious injury or damage to motorcycle*

**Advanced Sport Touring is not responsible for any injury or damage to property resulting from the use of this product*

Included with Luggage Rack: (1) Luggage Rack, (4) Short Spacers, Large steel bent bracket, Backrest pad with attached bracket, (2) 8mm bolts, (2) 12mm bolts

Tools you will need: 5mm Allen Key

- 1) Loosen and remove all (4) bolts holding luggage rack to motorcycle and the spacers. Keep these bolts. You will need them to install the new A.S.T. luggage rack. You will not use the spacers again. **(Fig. 1)**
- 2) Remove stock luggage rack and place aside.
- 3) Attempt to remove any debris from threads of bolts.
- 4) Place A.S.T. luggage rack on motorcycle while lining up holes of luggage rack to motorcycle.
- 5) Insert included spacers and the stock bolts.
- 6) Tighten down bolts to 18 ft-lbs.
- 7) Luggage Rack Installation Complete.
- 8) Attach large steel bent bracket to underside of the luggage rack using (2) 12mm bolts.
- 9) Attach backrest pad to large steel bent bracket using (2) 8mm bolts. You can attach it to any of the holes in the bracket on the backrest pad. **(Fig. 6).**

