

Ryker Rider Luggage Rack Installation Instructions (Bikes with Max Mount)

**Read ALL instructions BEFORE attempting to install this product*

**Failing to follow these instructions could result in serious injury or damage to motorcycle*

**Advanced Sport Touring is not responsible for any injury or damage to property resulting from the use of this product*

Included with Kit: (1) Luggage Rack, (1) Flat Steel Bracket (1) Post, (1) Hexagonal Mount

Required Tools for Installation: 4mm & 5mm Hex wrench

Hardware Included: (4) M6x12 Socket head, (2) M6x16 Socket head, (1) M6x10 Socket head, (2) M6x16 Pan head, (1) M8x20 Pan head, (1) M8x12 Button head.

- 1) Attach the POST only to either side of the Flat Steel Bracket with a M6x10 SH and a M8x12 BH bolt. Leave these loose. You'll tighten them at the end of the installation.
- 2) Attach the Flat Steel Bracket assembly you just worked on to the underside of the Max mount so that the POST protrudes through the top of the Max Mount using (4) M6x12 SH bolts. The threads are aluminum so you don't want to overtighten.
- 3) Place the Hexagonal Mount into the Hexagonal hole in the top of the Max Mount. Bolt it to the Flat Steel Plate by screwing the bolts from under the Max Mount with (2) M6x16 SH bolts. Leave these loose. You'll tighten them at the end of the installation.
- 4) Place the Luggage Rack on the mounts you just installed. There are two positions it can be mounted depending on how close you want it to yourself. Place (2) M6x16 PH bolts into the holes closest to the seat and (1) M8x20 PH bolt in the back hole. Straighten the Luggage Rack and tighten the bolts. Go back and tighten the bolts you left loose previously.
- 5) Go for a bunch of rides! Periodically, check the bolts to make sure everything is still where it's supposed to be. If you feel like something is loose, tighten it.
- 6) If at any point, you find yourself needing help. Let us know. We're happy to help.
 - QUICKEST RESPONSE TIME: CustomerService@AdvancedSportTouring.com
 - If you want to talk on the phone, call us at 813-938-1200 or just email us asking to talk on the phone and give us your phone number and we'll call you.





